

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 August 2005 (11.08.2005)


PCT

(10) International Publication Number
WO 2005/074164 A1

- (51) International Patent Classification⁷: **H04B 7/08**, 7/06, H04L 27/26
- (21) International Application Number: PCT/IB2005/050300
- (22) International Filing Date: 25 January 2005 (25.01.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
04100288.2 28 January 2004 (28.01.2004) EP
- (71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **DE RUIJTER, Hendricus, C.** [NL/US]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (74) Agents: **GROENENDAAL, Antonius, W., M. et al.**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: DIVERSITY SYSTEM FOR TRANSMITTING A SIGNAL WITH SUB-CARRIERS



(57) Abstract: In diversity systems (3) for transmitting signals (4) comprising sub-carriers from first units (1) to second units (2,2a), receivers (22,22a) coupled to antennas (25,26) located at different positions for receiving the signals (4) are provided with transforming modules (38,38a) for converting received antenna signals into sub-carrier-vectors per sub-carrier and per antenna (25,26) and processing modules (39,39a) for processing the sub-carrier-vectors per sub-carrier. Then, the received antenna signals are no longer splitted into arbitrary sub-bands, but they are splitted in accordance with the sub-carriers already present in the signal (4) to be transmitted. For transmitting return signals (5) comprising sub-carriers from the second units (2,2a) to the first units (1), transmitters (21,21 a) coupled to antennas (25,26) located at different positions for transmitting the return signals (5) are provided with reverse processing modules (49) for generating sub-carrier-vectors per sub-carrier and per antenna and with reverse transforming modules (48,48a) for converting the sub-carrier-vectors into antenna signals to be transmitted. The overall throughput of the diversity system (3) is improved.

WO 2005/074164 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*